

## Tynnvegget krympeslange, 3:1, Rull.

Selvslukkende, driftstemperatur – 55 + 135°C (125°C, 2:1)

Størrelse 51,0-102,0 har krympeområde 2:1

Veggtykkelse fra 0,55-1,4mm etter krymp.



El.nr	Størrelse	Farge	Lengde
1834876	3,0-1,0	Sort	30 M
1834877	6,0-2,0	Sort	30 M
1834878	9,0-3,0	Sort	30 M
1834879	12,0-4,0	Sort	30 M
1834880	19,0-6,0	Sort	30 M
1834881	24,0-8,0	Sort	30 M
1834882	39,0-12,0	Sort	30 M
1834812	51,0-25,4	Sort	15 M
1834813	76,0-38,0	Sort	25 M
1834814	102,0-51,0	Sort	25 M

El.nr	Størrelse	Farge	Lengde
1834834	3,0-1,0	Rød	30 M
1834835	6,0-2,0	Rød	30 M
1834836	9,0-3,0	Rød	30 M
1834837	12,0-4,0	Rød	30 M
1834838	19,0-6,0	Rød	30 M
1834839	24,0-8,0	Rød	30 M
1834841	39,0-12,0	Rød	30 M
1834842	51,0-25,4	Rød	30 M
1834843	76,0-38,0	Rød	15 M
1834844	102,0-51,0	Rød	15 M

1834864	3,0-1,0	Blå	30 M
1834865	6,0-2,0	Blå	30 M
1834866	9,0-3,0	Blå	30 M
1834867	12,0-4,0	Blå	30 M
1834868	19,0-6,0	Blå	30 M
1834869	24,0-8,0	Blå	30 M
1834871	39,0-12,0	Blå	30 M
1834872	51,0-25,4	Blå	30 M
1834873	76,0-38,0	Blå	15 M
1834874	102,0-51,0	Blå	15 M

1834849	3,0-1,0	Hvit	30 M
1834850	6,0-2,0	Hvit	30 M
1834851	9,0-3,0	Hvit	30 M
1834852	12,0-4,0	Hvit	30 M
1834853	19,0-6,0	Hvit	30 M
1834854	24,0-8,0	Hvit	30 M
1834856	39,0-12,0	Hvit	30 M
1834857	51,0-25,4	Hvit	30 M
1834858	76,0-38,0	Hvit	15 M
1834859	102,0-51,0	Hvit	15 M

1834888	3,0-1,0	Klar	30 M
1834889	6,0-2,0	Klar	30 M
1834890	9,0-3,0	Klar	30 M
1834891	12,0-4,0	Klar	30 M
1834892	19,0-6,0	Klar	30 M
1834893	24,0-8,0	Klar	30 M
1834894	39,0-12,0	Klar	30 M
1834896	51,0-25,4	Klar	30 M
1834897	76,0-38,0	Klar	15 M
1834898	102,0-51,0	Klar	15 M

1834899	3,0-1,0	Gul/grønn	30 M
1834901	6,0-2,0	Gul/grønn	30 M
1834902	9,0-3,0	Gul/grønn	30 M
1834903	12,0-4,0	Gul/grønn	30 M
1834904	19,0-6,0	Gul/grønn	30 M
1834905	24,0-8,0	Gul/grønn	30 M
1834906	39,0-12,0	Gul/grønn	30 M
1834908	76,0-38,0	Gul/Grønn	25 M

