

## Tynnvegget krympeslange, 3:1, på Spoleboks.

Selvslukkende, driftstemperatur – 55 + 135°C

Materiale: Polyolefin,

Vegtykkelse: fra 0,55 til 1,0mm



El.nr.	Størrelse	Farge	Lengde
1835601	3,0-1,0	Sort	10 M
1835602	6,0-2,0	Sort	7 M
1835603	9,0-3,0	Sort	5 M
1835604	12,0-4,0	Sort	4 M
1835605	19,0-6,0	Sort	3 M
1835606	24,0-8,0	Sort	3 M

El.nr.	Størrelse	Farge	Lengde
1835609	3,0-1,0	Rød	10 M
1835610	6,0-2,0	Rød	7 M
1835611	9,0-3,0	Rød	5 M
1835612	12,0-4,0	Rød	4 M
1835613	19,0-6,0	Rød	3 M
1835614	24,0-8,0	Rød	3 M

El.nr.	Størrelse	Farge	Lengde
1835619	3,0-1,0	Blå	10 M
1835620	6,0-2,0	Blå	7 M
1835621	9,0-3,0	Blå	5 M
1835622	12,0-4,0	Blå	4 M
1835623	19,0-6,0	Blå	3 M
1835624	24,0-8,0	Blå	3 M

El.nr.	Størrelse	Farge	Lengde
1835628	3,0-1,0	Hvit	10 M
1835629	6,0-2,0	Hvit	7 M
1835630	9,0-3,0	Hvit	5 M
1835631	12,0-4,0	Hvit	4 M
1835632	19,0-6,0	Hvit	3 M
1835633	24,0-8,0	Hvit	3 M

El.nr.	Størrelse	Farge	Lengde
1835637	3,0-1,0	Klar	10 M
1835638	6,0-2,0	Klar	7 M
1835639	9,0-3,0	Klar	5 M
1835640	12,0-4,0	Klar	4 M
1835641	19,0-6,0	Klar	3 M
1835642	24,0-8,0	Klar	3 M

El.nr.	Størrelse	Farge	Lengde
1835645	3,0-1,0	Gul/grønn	10 M
1835646	6,0-2,0	Gul/grønn	7 M
1835647	9,0-3,0	Gul/grønn	5 M
1835648	12,0-4,0	Gul/grønn	4 M
1835649	19,0-6,0	Gul/grønn	3 M
1835650	24,0-8,0	Gul/grønn	3 M

## Tynnvegget krympeslange, 3:1, på Spoleboks, med lim

Driftstemperatur – 55 + 110°C

Materiale: Polyolefin,

Vegtykkelse: fra 1,0 til 2,4mm

El.nr.	Størrelse	Farge	Lengde
1835670	3,0-1,0	Sort	5 M
1835671	6,0-2,0	Sort	3,5 M
1835672	9,0-3,0	Sort	3 M
1835673	12,0-4,0	Sort	2,5 M
1835674	19,0-6,0	Sort	2 M
1835675	24,0-8,0	Sort	1,5 M



Klar er ikke selvslukkende