



Type	Art.-no.	L (mm)	Weight (kg)	Qty. of rivet and washer
1	4265.04/660	100	approx. 1,5	1
2	4265.04/661	125	approx. 1,7	1
3	4265.04/662	150	approx. 2,0	1
4	4265.04/663	200	approx. 2,5	2
5	4265.04/664	250	approx. 3,0	2
6	4265.04/665	300	approx. 3,4	2
7	4265.04/666	350	approx. 3,7	2
8	4265.04/667	400	approx. 4,1	2
9	4265.04/668	450	approx. 4,6	2
10	4265.04/669	500	approx. 5,2	2
11	4265.04/670	325	approx. 3,5	2
12	4265.04/671	140	approx. 1,9	1
13	4265.04/672	1000	approx. 10,1	2
14	4265.04/673	225	approx. 2,8	2
15	4265.04/674	175	approx. 2,2	2
16	4265.04/675	375	approx. 3,9	2
17	4265.04/676	750	approx. 7,5	2
18	4265.04/677	575	approx. 5,8	2
19	4265.04/678	650	approx. 6,7	2
20	4265.04/679	600	approx. 6,1	2
21	4265.04/680	725	approx. 7,7	2
22	4265.04/681	275	approx. 3,2	2
23	4265.04/682	425	approx. 4,3	2
24	4265.04/683	475	approx. 4,8	2
25	4265.04/684	530	approx. 5,5	2
26	4265.04/685	340	approx. 3,3	2
27	4265.04/686	850	approx. 8,6	2

4 s.t. Rivet	DIN 661	Al
3 s.t. Washer A10,5	DIN 125	Steel
2 1 Bolt S22	DIN 48073	8,8 hot dip galv.
1 2 Strap	Standard	Steel hot dip galv.
1 1m Qty Description	Standard	Art. no.
2013. Date	Name	Material
Drawn 13.06.	Checked - -	Gr/imm
Replace for		
Replaced by		
Art. No.	s. Tab.	

Type	Drng. No.	Rev. Mod.
K	F0312059	p
Title		Page
Clevis eye straight		A3
DIN 48 078		No. of pages
Scale		
NTS		

Tolerance acc. to: ISO 2768-VL Short circuit current: 50 kA 1s Breaking load: 320 kN Mass: s. Tab.

Letter	Revision	Date	Name
p	Indexpassung ohne Änderung	13.06.2013	Gr/imm
<p>This page and its indications is intellectual property of Mosdorfer Company and it is not allowed to forward those information to a third party without the written consent of Mosdorfer company.</p>			
Number	Modification	Date	Name