



φ24,5-28,0
 MO-LL-EA
 MA 40
 F1001058
 MM/JJ XX

Item	Qty	Description	Standard	Drq. no.	Art. no.	Material	Surface	Mass [kg]
7	1	washer φ30/13/3			1054-91	A2	stainless	
6	1	hexagon screw M12x45	DIN 933		1009-46/4	A2-F80	stainless	
5	1	steel wire φ10,15			01005003 A3	ZS 100.026	st	not dip galv.
4	1	damper weight 1,0 kg			01001003 A3	ZD 005.034 G	EN-JL 1040	hot dip galv.
3	1	damper weight 0,6 kg			01001002 A3	ZD 005.035 G	EN-JL 1040	hot dip galv.
2	1	counter piece φ24,5-28,0			134-614-532	EN-AW 6082 16		
1	1	clamp φ24,5-28,0 mm			134-623-328	EN-AW 6082 15		



Name: *F. Faul*
 Checked: 24.05.09
 Title:

1996	Date	Replace for	Sim. to drq.-no.
23.05.	Drawn	Replaced by	F1001057 A3
24.05.	Checked	Art. No.	9303.070/EA1
		Drq. No.	F1001058
		Rev. Mod.	c
		No. of pages	A3

Scale: 1:2
 Title: Stockbridge damper
 for cond. φ24,5-28,0 mm
 Breaking load: --- kN
 Mass: appr. 2,4 kg
 Short circuit current: --- kA 1s
 Tolerance acc. to: ISO 2768 v

Letter	Revision	Date	Name
c	Suppl. code added.	09.09.09	F. Faul
b	Anzugsdrehmoment 40Nm (75Nm)	28.11.01	Zechner
d	4403(420x5),134-623-328(134-614-522)	14.06.96	Gr. Im

This page and its indications is intellectual property of Mosdorfer Company and it isn't allowed to forward those information to a third party without the written assent of Mosdorfer company.