



Dimensions after compression

Al - sleeve

St - sleeve

Minimum failing load = 95% of UTS of conductor.

The steel-sleeve is filled with compound and closed by a plug.
The compound for the al-sleeve is added in tubes.1 tube (250)g) for 3 sleeves.

Item	Qty	Description	Standard Drg. no.	Art. no.	Material	Surface	Mass [kg]
3	2	Plug			plastic		
2	1	St-sleeve ø17/ø9,6/130			C 45 E + N	hot dip galv.	
1	1	Al-sleeve ø46/ø29,5/580			AlMgSi0,5F13		

1997	Date	Name	MOSDORFER AUSTRIA
Drawn	25.06.		
Checked	-11-		
Scale	1:1,5		

Title: Compression joint for ACSR "CONDOR"

Replace for	20.721 A3
Replaced by	
Art. No.	4854.60
Drg. No.	F1101046
Rev.	a
Mod.	
Sim. to drg.-no.	
No. of pages	
Page	A3

Tolerance acc. to: ISO 2768 c | Short circuit current: --- kA 1s | Breaking load: --- kN | Mass: approx. 1,8 kg

Letter	Revision	Date	Name
0	Zng. überarbeitet	10.11.2005	Gr/Jöbl

Number	Modification	Date	Name

This page and its indications is intellectual property of MOSDORFER. Copying and/or disclosure of these information to a third party without the written consent of MOSDORFER company.