


Product name	2F Blown fiber EPSU SM G657A1 Yellow HDPE 1,2mm 6km/pan, S12
Product code	5042434
Product type	EPSU 2XG657A1 YE
GTIN	7332811193835
ETIM-Class	EC000034



PRODUCT SPECIFICATIONS

2F SM G657A1 EPSU air blown optical fibre is typically used in micro duct installation applications. ABF can utilize in existing and new duct systems more effectively by accommodating more fibres in given subduct network. The fiber units is suitable for air-blown installation. Cable parameters such as cable diameter, stiffness and sheath friction is optimized for best installation performance. The expected service life in normal use exceeds 30 years.

Measurements

Length	1 000 mm
Height	1,2 mm
Width	1,2 mm
Weight	1,4 g

Physical Characteristics

Fibre Count	2
Cable Construction	Acrylat
Fibre Type	ITU-T G.657 A1
Fibre Colour Sequence	S12
Outer Sheath Material	HDPE (High Density Polyethene)
Colour of Cable Sheath	Yellow
Cable Diameter	1,2 mm
Cable Diameter Tolerance	+/- 0.2 mm

Nominal Cable Weight	1,4 kg/km
----------------------	-----------

Mechanical & Environmental Characteristics

Halogen Free	Yes
Metal free	Yes
Tensile Strength (N) IEC-60794-1-21-E1	13 N
Crush Resistance - IEC- 60794-1-21-E3	100 N/10cm
Min. Bend Radius (During Installation) IEC-60794-1-21-E11	40 mm
Temperature Performance Installation IEC-60794-1-22-F1	-15°C till +50°C*
Temperature Performance Operation IEC-60794-1-22-F1	-40°C till +60°C
Temperature Performance Storage IEC-60794-1-22-F1	-40°C till +60°C