

Produktnamn	Fiberkablage SM DPX 2xLC/UPC-LC/UPC G657A BLÅ 2mm LSZH 2m
E-nummer	5077432
GTIN	7332811074257
ETIM-klass	EC001263



PRODUKTSPECIFIKATIONER

Fiberoptic patch cord singlemode G657A with blue 2mm duplex cable and SC/UPC-SC/UPC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols

Mått

Längd	180 mm
Höjd	10 mm
Bredd	210 mm
Vikt	27 g

Tekniska Specifikationer - Kontakter

Max dämpning per kontakt (UPC)	0,2 dB
Max reflektionsdämpning på UPC kontakt	-55 dB
Radius of Curvature UPC	7-25 mm
Max Vertex Offset	50 µm
Fiber instick/utstick (nm)	0 +/- 50 nm

Tekniska Specifikationer - Kablage

Längd	2 m
Fibertyp	ITU-T G.657 A1
Yttermantelets Material	LSZH (Low Smoke Zero Halogen)
Yttermantelets Färg	Blå
Kabeldiameter	2 mm
Temperaturområde vid Användning	-40°C till +85°C
Temperaturområde vid Lagring & Transport	-40°C till +85°C
Max Installationskraft	97 N
Halogenfri	Ja