

Product name	Ultima connect left "handed" ring section 750×750mm .
Product code	0666664
GTIN	7332811342875
ETIM-Class	EC004532



## Measurements

Length	885 mm
Height	150 mm
Width	885 mm
Weight	19 440 g

## Technical Specifications - Chambers

Product group	Chamber section
Material	Glass Reinforced Polyester (GRP)
Material Color	Gray
Tensile Strength (ISO 527)	45 MPA
Flexural Modulus (ISO 14125)	9,5 GPA
Impact Strength (ISO 179)	50 KJ/m <sup>2</sup>
Density (ISO 1183-1)	1,78 g/cm <sup>3</sup>
Service Temperature	-40 to 110°C
Surface Resistivity	1,00e+14 ohm
Volume Resistivity	1e+12 ohm/cm
Fire Performance (UL94)	hb rating
Heat deflection temperature (ISO 75-2)	200 °C
Water Absorption (Non polar polymer) (ISO 62)	0,5 %
Limited Oxygen Index (ISO 4589)	23 %
Vertical loads EN124	F900
External Length	885 mm

External Width	885 mm
External Hight	150 mm
Internal Length	750 mm
Internal Width	750 mm
Internal Hight	150 mm

### Sustainability

product.sustainability-label.epd	Yes
----------------------------------	-----