

<b>Product name</b>	Ultima connect access chamber 900x600x900mm
<b>Product code</b>	0666916
<b>GTIN</b>	7332811351891
<b>ETIM-Class</b>	EC004532



## Measurements

<b>Length</b>	735 mm
<b>Height</b>	900 mm
<b>Width</b>	1 035 mm
<b>Weight</b>	117 600 g

## Technical Specifications - Chambers

<b>Product group</b>	Chamber section
<b>Material</b>	Glass Reinforced Polyester (GRP)
<b>Material Color</b>	Gray
<b>Tensile Strength (ISO 527)</b>	45 MPA
<b>Flexural Modulus (ISO 14125)</b>	9,5 GPA
<b>Density (ISO 1183-1)</b>	1,78 g/cm <sup>3</sup>
<b>Service Temperature</b>	-40 to 110 °C
<b>Surface Resistivity</b>	1,00e+14 ohm
<b>Volume Resistivity</b>	1e+12 ohm/cm
<b>Fire Performance (UL94)</b>	hb rating
<b>Heat deflection temperature (ISO 75-2)</b>	200 °C
<b>Water Absorption (Non polar polymer) (ISO 62)</b>	0,5 %
<b>Limited Oxygen Index (ISO 4589)</b>	23 %
<b>Vertical loads EN124</b>	F900
<b>External Length</b>	1 035 mm
<b>External Width</b>	735 mm

<b>External Hight</b>	900 mm
<b>Internal Length</b>	900 mm
<b>Internal Width</b>	600 mm
<b>Internal Hight</b>	900 mm