

|                     |                              |
|---------------------|------------------------------|
| <b>Product name</b> | Low voltage heatshrink joint |
| <b>Product code</b> | 0703102                      |
| <b>Product type</b> | MPS 53                       |
| <b>GTIN</b>         | 7332811323485                |
| <b>ETIM-Class</b>   | EC001169                     |



## Measurements

|               |        |
|---------------|--------|
| <b>Length</b> | 550 mm |
| <b>Height</b> | 80 mm  |
| <b>Width</b>  | 120 mm |
| <b>Weight</b> | 500 g  |

## Technical Specifications - Joint 1kV

|                              |                  |
|------------------------------|------------------|
| <b>Voltage</b>               | 1 kV             |
| <b>Number of Conductors</b>  | 5                |
| <b>Incl Contact Material</b> | Mechanical       |
| <b>Incl. Liners</b>          | No               |
| <b>Insulation Type</b>       | Heat Shrink Tube |
| <b>Halogen Free</b>          | Yes              |

## Cable specifications for contact material

|                                 |                       |
|---------------------------------|-----------------------|
| <b>Aluminum Stranded</b>        | 10-50 mm <sup>2</sup> |
| <b>Aluminum Sector Stranded</b> | 35-50 mm <sup>2</sup> |
| <b>Aluminum Solid</b>           | 10-50 mm <sup>2</sup> |
| <b>Aluminum Sector Solid</b>    | 35-50 mm <sup>2</sup> |
| <b>Copper Stranded</b>          | 6-50 mm <sup>2</sup>  |
| <b>Copper Sector Stranded</b>   | 35-50 mm <sup>2</sup> |

|                              |                      |
|------------------------------|----------------------|
| Copper Solid                 | 6-50 mm <sup>2</sup> |
| Copper Class 5 multistranded | 6-50 mm <sup>2</sup> |

## Application

|                          |             |
|--------------------------|-------------|
| Plastic Insulated Cables | Yes         |
| Paper Insulated Cables   | No          |
| Installation Type        | Straight    |
| Type                     | Heat Shrink |