

| | |
|---------------------|------------------------------|
| Product name | Low voltage heatshrink joint |
| Product code | 0703108 |
| Product type | MPS 62 |
| GTIN | 7332811323546 |
| ETIM-Class | EC001169 |



Measurements

| | |
|---------------|---------|
| Length | 850 mm |
| Height | 120 mm |
| Width | 120 mm |
| Weight | 1 200 g |

Technical Specifications - Joint 1kV

| | |
|------------------------------|------------------|
| Voltage | 1 kV |
| Number of Conductors | 4 |
| Screen | Yes |
| Incl Contact Material | Mechanical |
| Incl. Liners | No |
| Insulation Type | Heat Shrink Tube |
| Halogen Free | Yes |

Cable specifications for contact material

| | |
|---------------------------------|-----------------------|
| Aluminum Stranded | 16-25 mm ² |
| Aluminum Sector Stranded | 35-95 mm ² |
| Aluminum Solid | 16-95 mm ² |
| Aluminum Sector Solid | 16-95 mm ² |
| Copper Stranded | 16-95 mm ² |

| | |
|-------------------------------------|-----------------------|
| Copper Sector Stranded | 35-95 mm ² |
| Copper Solid | 16-95 mm ² |
| Copper Class 5 multistranded | 16-50 mm ² |

Application

| | |
|---------------------------------|-------------|
| Plastic Insulated Cables | Yes |
| Installation Type | Straight |
| Type | Heat Shrink |