

<b>Product name</b>	Conductor 593 mm <sup>2</sup> Curlew Al 54/3.52 mm + St 7/3.52
<b>Product code</b>	1112010-S002
<b>GTIN</b>	7332811335235
<b>ETIM-Class</b>	



## Measurements

<b>Weight</b>	1 990 g
---------------	---------

## Technical Specifications

<b>Type</b>	acsr
<b>Code</b>	525-al1/68-st1a
<b>Old Code</b>	593 curlew
<b>Al Cross Section</b>	526,5 mm <sup>2</sup>
<b>Cross Section Steel</b>	68,1 mm <sup>2</sup>
<b>Cross Section Total</b>	593,6 mm <sup>2</sup>
<b>Number of Wires Al</b>	54
<b>Number of Wires Steel</b>	7
<b>Wire Diameter Al</b>	3,52 mm
<b>Wire Diameter Steel</b>	3,52 mm
<b>Diameter Core</b>	10,6 mm
<b>Conductor Diameter</b>	31,7 mm
<b>Mass per Unit Al</b>	1453,3 kg/km
<b>Mass per Unit Steel</b>	532,7 kg/km
<b>Mass per Unit Total</b>	1986,0 kg/km
<b>Rated Strength</b>	159,01 kN
<b>DC Resistance</b>	0,0550 Ω/km