

<b>Product name</b>	Conductor 774 mm <sup>2</sup> Skata, Al 54/4.02 mm + St 7/4.02
<b>Product code</b>	1112010-S012
<b>GTIN</b>	7332811341748
<b>ETIM-Class</b>	



## Measurements

<b>Length</b>	1 000 mm
<b>Weight</b>	2 590 g

## Technical Specifications

<b>Type</b>	acsr
<b>Code</b>	685-all/89-st1a
<b>Old Code</b>	774 skata
<b>Al Cross Section</b>	685,4 mm <sup>2</sup>
<b>Cross Section Steel</b>	88,8 mm <sup>2</sup>
<b>Cross Section Total</b>	774,2 mm <sup>2</sup>
<b>Number of Wires Al</b>	54
<b>Number of Wires Steel</b>	7
<b>Wire Diameter Al</b>	4,02 mm
<b>Wire Diameter Steel</b>	4,02 mm
<b>Diameter Core</b>	12,1 mm
<b>Conductor Diameter</b>	36,2 mm
<b>Mass per Unit Al</b>	1895,7 kg/km
<b>Mass per Unit Steel</b>	694,5 kg/km
<b>Mass per Unit Total</b>	2590,2 kg/km
<b>Rated Strength</b>	207,39 kN
<b>DC Resistance</b>	0,0422 Ω/km

