

|              |  |
|--------------|--|
| Product name | UV-resistant cable tie 4,8×700MM - with steel tongue |
| Product code | 1518594  |
| GTIN         | 7332811386350  |
| ETIM-Class   | EC000046   |



## PRODUCT SPECIFICATIONS

Cable ties for outdoor use, made of UV-resistant polyamide, are ideal for solar energy applications and demanding environments.

With a self-locking mechanism, they ensure a strong and reliable band closure and have wide application in the automotive, energy, and food industries.

The cable ties are internally ribbed for easy handling.

## Measurements

|        |         |
|--------|---------|
| Length | 35 mm   |
| Height | 820 mm  |
| Width  | 100 mm  |
| Weight | 0,475 g |

## Technical Specifications - Cable tie

|                      |        |
|----------------------|--------|
| Band width           | 4,8 mm |
| Length belt/tape/tie | 700 mm |
| Tie thickness        | 1,2 mm |

|   |                  |
|---|------------------|
| Bundle diameter   | 3.5 – 210 mm     |
| Min. tensile strength   | 360 mm           |
| Operating temperature   | -40 – 105 °C     |
| Mounting temperature  | -40 – 105 °C     |
| Model   | Without toothing |
| Band closure  | Other            |
| Material  | Plastic          |
| Material quality  | Polyamide (PA)   |
| Surface protection  | Untreated        |
| Halogen free  | Yes              |
| Colour  | Black            |
| Transparent   | No               |
| Fluorescent   | No               |
| Detectable  | No               |
| Text strip  | None             |
| Releasable closure  | No               |
| Type of fastening   | None             |
| VG approval   | No               |
| MIL approval  | No               |
| UL approval   | No               |
| Inflammability class of insulation material according to UL94 | V2               |