

| | |
|---------------------|---|
| Product name | Patch SM SPX 1xSC/APC-LC/UPC G657A2 White 4mm LSZH 1m |
| Product code | 5066769 |
| GTIN | 7332811389085 |
| ETIM-Class | EC001263 |



PRODUCT SPECIFICATIONS

Fiber optic patch cord singlemode G657A2 with white 4mm simplex cable and SC/APC-LC/UPC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols.

Measurements

| | |
|---------------|--------|
| Length | 210 mm |
| Height | 15 mm |
| Width | 180 mm |
| Weight | 19 g |

Technical Specifications - Connectors

| | |
|--|--------|
| Max insertion loss per connector (UPC) | 0,2 dB |
| Max insertion loss per connector (APC) | 0,3 dB |
| Max Optical Return Loss for UPC connector | -55 dB |
| Max Optical Return Loss for APC connector | -65 dB |
| Radius of Curvature APC | 5-12 |
| Radius of Curvature UPC | 7-12 |

| | |
|-------------------|-------|
| Max Vertex Offset | 50 µm |
|-------------------|-------|

Technical Specifications - Patch Cords

| | |
|--|-------------------------------|
| Fibre Type | ITU-T G.657 A2 |
| Outer Sheath Material | LSZH (Low Smoke Zero Halogen) |
| Cable Diameter | 4 mm |
| Temperature ranges for Operation | -40°C to +85°C |
| Temperature ranges for transport and storage | -40°C to +85°C |
| Halogen Free | Yes |