

Product name	Patch SM.SPX 1xSC/APC-LC/UPC G657A2 White 4mm LSZH 3m
Product code	5066771
GTIN	7332811389108
ETIM-Class	EC001263



PRODUCT SPECIFICATIONS

Fiber optic patch cord singlemode G657A2 with white 4mm simplex cable and SC/APC-LC/UPC connectors.

Halogen-free according to EN 60754-1/2 and flame-retardant according to IEC 60332-2-2. Meets the requirements of IEC 61300, EN186000-1, EIA/TIA-455 and TELCORDIA GR-326-CORE/GR-63.

ID marked with a unique number for full traceability and delivered with individual measurement protocols.

Measurements

Length	210 mm
Height	15 mm
Width	180 mm
Weight	47 g

Technical Specifications - Connectors

Max insertion loss per connector (UPC)	0,2 dB
Max insertion loss per connector (APC)	0,3 dB
Max Optical Return Loss for UPC connector	-55 dB
Max Optical Return Loss for APC connector	-65 dB
Radius of Curvature APC	5-12
Radius of Curvature UPC	7-12

Max Vertex Offset	50 µm
-------------------	-------

Technical Specifications - Patch Cords

Fibre Type	ITU-T G.657 A2
Outer Sheath Material	LSZH (Low Smoke Zero Halogen)
Cable Diameter	4 mm
Temperature ranges for Operation	-40°C to +85°C
Temperature ranges for transport and storage	-40°C to +85°C
Halogen Free	Yes