

<b>Product name</b>	Aurora Multilite 30m for the wireless monitored Aurora light family
<b>Product code</b>	7347887
<b>GTIN</b>	7332811380730
<b>ETIM-Class</b>	EC001957



## Measurements

<b>Length</b>	45 mm
<b>Height</b>	227 mm
<b>Width</b>	330 mm
<b>Weight</b>	1 080 g

## Technical Specifications - Batteries

<b>Voltage</b>	3,2 V
<b>Capacity</b>	1 600 mAh
<b>Type</b>	Li-FePo4
<b>Dimensions</b>	65x19x19 mm
<b>Rechargeable</b>	Yes
<b>Charging Time</b>	48 h
<b>Estimated Lifetime</b>	10 Year
<b>Cell Type</b>	18650
<b>Number of Cells</b>	1

## Technical Specifications - Pictograms

<b>Shape</b>	Rectangular
<b>Model</b>	Shield
<b>Material</b>	Plastic

UV resistant	Yes
Halogen Free	Yes
Waterproof	No
With alert-/information symbol	Yes
Symbol	Arrow
With alert-/information text	Yes
Type of fastening	Clamp
With mounting material	Yes
Colour	Green
Fluorescent	No
Photoluminescent (glow in the dark)	No
Mounting method	Free-hanging

## Technical Specifications - Emergency luminaire

Mounting method	Wall surface mounting/ceiling surface mounting
Function	Escape route lighting/signage
Suitable for labelling type	Insert sheet/plate
Type of indicator	Single/double-sided
With pictogram	Yes
Suitable for continuous circuit	Yes
Emergency function monitoring system	Other
Emergency power supply system	Peripheral (individual battery)
Battery technology	Lithium-ions
Type of lithium-ion battery	Lithium iron phosphate (LiFePO4)
With heating element for battery	No
Lamp type	LED not exchangeable
With light source	Yes
Number of lighting heads	20
Housing material	Plastic
RAL-number housing	9003
Housing colour	White
Material cover	Plastic, transparent
Voltage type	AC
Nominal voltage	230 V
Degree of protection (IP)	IP40
Impact strength	IK04
Protection class according to IEC 61140	II
Rated ambient temperature according to IEC 62722-2-1	5 – 40 °C
Colour temperature	6,500 – 6,500 K
Recognition distance	30 m

<b>Nominal operation time</b>	1 – 3 h
<b>Width</b>	310 mm
<b>Height/depth</b>	160 mm
<b>Number of poles</b>	2
<b>Conductor cross section</b>	2,5 mm <sup>2</sup>
<b>Connection type</b>	Plug-in connection