

Lina FeAl



Produkt-/E-nummer	Produktnamn	Kod	Ledardiameter	Brottlast
1112010-S002	Lina 593 mm ² Curlew Al 54/3.52 mm + St 7/3.52	525-al1/68-st1a	31,7 mm	159,01 kN
1112010-S008	Lina 99 mm ² Pigeon Al 6/4.25 mm + St 1/4.25	85-al1/14-st1a	12,8 mm	29,22 kN
1112010-S009	Lina 157 mm ² Partridge Al 26/2.57 mm + St 7/2.00	135-al1/22-st1a	16,3 mm	48,66 kN
1112010-S011	Lina 241 mm ² Atle, Al 12/4.02 mm + St 7/4.02	152-al1/89-st1a	20,1 mm	122,10 kN
1112010-S012	Lina 774 mm ² Skata, Al 54/4.02 mm + St 7/4.02	685-al1/89-st1a	36,2 mm	207,39 kN
1141010-S002	Lina 142 mm ² Dotterel Al 12/3.08 mm + St 7/3.08	89-al1/52-st1a	15,4 mm	72,12 kN
1141010-S003	Lina 329mm ² FeAl Dove AL 26/3.72 mm + ST 7/2.89 mm	283-al1/46-st1a	23,6 mm	97,56 kN
1141010-S004	Lina 910 mm ² Falcon AL54/4.36mm + st 19/2.62	806-al1/102-st1a	39,3 mm	245,77 kN
1141010-S005	Lina 319 mm ² Ymer Al 32/3.16mm + st 7/3.52	251-al1/65-st1a	22,9 mm	112,56 kN
33300204	Lina 593 mm ² Morkulla Al 42/4,13 mm + St7/2,31	563-al1/29-st1a	31,7 mm	123,47 kN
33300205	Lina 234 mm ² Ibis Al 26/3,14 mm + St 7/2,44	201-al1/33-st1a	19,9 mm	70,53 kN